



SP-401P PORTABLE RUNWAY EDGE LIGHT

MEDIUM INTENSITY



		Compliance: ICAO Annex 14 Vol. I (7th. Edition, July 2016)
---	---	--

FEATURES

- 180 hrs of autonomy
- Remote activation
- Convertible to solar airfield light
- 1.200 cd light output

APPLICATION

- Mobile airfield light designed to quickly illuminate temporary airfield in accordance with ICAO:
- Temporary runways
 - Remote airfields
 - Backup airport lighting
 - Emergency landing airstrips

TECHNICAL SPECIFICATIONS

Optics	
	<ul style="list-style-type: none"> • 1.200 cd light output (tested by accredited laboratory) • Combined type, omnidirectional and bidirectional • LED lifespan: 100.000 hrs • Maximum power consumption: 9W • NVG-compatible (optional) • Color: white/ white • User-replaceable
Battery	
Standard battery	<ul style="list-style-type: none"> • 2x built-in batteries, user-replaceable, air transportable • Autonomy: 180 hrs (minimum intensity) • Total capacity: 216W (2x9Ah/12V) • Deep-cycle VRLA, 12V/9Ah (available worldwide) • Lifespan: 1.200 cycles (designed for 4-5 years)
Cyclon battery (Arctic Pack)	<ul style="list-style-type: none"> • 1x built-in battery, user-replaceable, air transportable • Autonomy: 100 hrs (minimum intensity) • Total capacity: 120W (10Ah/12V) • Lifespan: 300 cycles (designed for 10-15 years)
Charging	
	<ul style="list-style-type: none"> • Via OCT-401 Charger (charging time: 8 hrs) • Contactless charging in a Trailer (charging time: 8 hrs) • Optional: solar power supply
Remote Activation & Control	
	<ul style="list-style-type: none"> • Wireless mesh type network • Operating frequency: 868 MHz (optional 2.4GHz or 433 Mhz) • Operating range: up to 1.5 km, relayed (each light is a repeater)
	Operating Modes: <ul style="list-style-type: none"> • Steady / Flashing / Dusk till dawn • Visible / Infrared (optional) / Visible + Infrared (optional)
	Remote activation: <ul style="list-style-type: none"> • Via UR-101 Handheld Controller • Via UR-201 Control & Monitoring Unit <ul style="list-style-type: none"> GSM activation (Cell Phone) VHF activation (Air-band Radio) • Via ALCMS Computer Interface (requires UR-201)
Casing & Components	
Materials	<ul style="list-style-type: none"> • Dome: glass, UV-resistan • Casing: Lexan polycarbonate, UV-stabilized, color: aviation yellow • Carrying handle: polycarbonate
	<ul style="list-style-type: none"> • Detachable antenna • Pressure stabilizing valve, transportation fuse • Battery level indicator • Transport circuit breake • Casing lifespan: 15 years • Optional: frangiblmounting (tested by accredited laboratory) • Dimensions (LxWxH): 244 mm x 185 mm x 297 mm • Weight: 7 kg

Safety & Reliability	
	<ul style="list-style-type: none"> • Five levels of protection against system failure • Secondary power supply: backup battery • Real-time monitoring via ALCMS (Airfield Lighting Control and Monitoring System) • Emergency ON/OFF button
Environmental Conditions	
	<ul style="list-style-type: none"> • Temperature range: -20 to 50 °C (-4 to 122 °F) • Optional: -40 to 80 °C (-40 to 176 °F) • Ingress protection: IP-67 (tested by accredited laboratory) • Impact Resistance: IK-10 (tested by accredited laboratory) • Jet Blast Resistance: 240 kph (tested by accredited laboratory)
Compliance	
Photometric & Chromaticity	ICAO, Annex 14th, Volume I, 7th Edition dated July 2016, clause 5.3.9.8 & clause 5.3.9.9, Appendix 1, Figure A1-1b
Jet Blast Resistance	ICAO, Annex 14th, Volume I, 8th Edition dated July 2018. Doc 9157, Part 6, clause 3.2.2 & clause 4.9.1. FAA AC 150/5345-50B dated September 2007, clause 3.2.2
Frangibility	ICAO Doc 9157 AN901 Aerodrome Design Manual Part 6, 1st Edition dated 2006, clause 4.9 ICAO, Annex 14th, Volume I, 8th Edition dated July 2018, clause 5.3.1.3 FAA AC 150-5345-46E clause 3.4.2.1 FAA AC 150/5220-23, clause 3.2
Secondary Power Supply	ICAO, Annex 14th, Volume I, 7th Edition dated July 2016, clause 8.1.8-8.1.9 & clause 8.1.11
CE Declaration of Conformity	2014/53/EU RED Directive, clauses 3.1a, 3.1b, 3.2 2011/65/EU ROHS Directive, clause 4.1

Accredited Laboratory Testing

Photometric & Chromaticity	Intertek Laboratory
Jet Blast Resistance	Warsaw Institute of Aviation The Laboratory of Aerodynamics
Frangibility	Laborex Research Laboratory
Ingress Protection	EMAG Institute of Innovative Technologies
Impact Resistance	Laborex Research Laboratory
Electromagnetic Compatibility	Military Institute of Armament Technology

